

石頭金

**MetalMiracle<sup>®</sup>**

Slewing Bearing with outer flange and internal gear including but not limited to:



			216	340	39	324	252	20	20	M6	M6	310	238	30	5	34	34	279	277	4	56	224	300	10
VLI200414N ZT			325	518	56	490	375	8	12	φ18	M12	458.5	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335	600	28.5
VLI 20 0414N ZT RL2			325	516	56	490	375	8	12	φ18	M12	456	350	40	11.5	44.5	47.5	415.5	412.5	5	67	335	300	36.3
VLI200414N			325	518	56	490	375	8	12	18	M12		350	40	8.5	44.5	47.5	415.5	412.5	5	67	335	295	27.5
	232.20.0400.013		326.5	518	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335	250	27.1
	232.20.0400.503		326.5	518	56	490	375	16	12	18	M12			45.5	10.5	45.5	45.5	415.5	412.5	5	67	335	250	26.9
	232.21.0475.013		326.5	517	56	490	375	8	12	18	M12			45.5	10.5	45.5	45.5	415.5	411	5	67	335	250	27.1
		1.505.20.00.C	326.5	518	56	490	375	8	12	φ18	M12	453		46	10	46	46	415.5	412.5	5	67	335	500	35.4
VLI200544N ZT			444	648	56	620	505	10	16	φ18	M12	588.5		44.5	11.5	44.5	47.5	545.5	542.5	6	76	456	790	40.6
VLI200544N			444	648	56	620	505	10	16	18	M12			44.5	11.5	44.5	47.5	545.5	542.5	6	76	456	385	38
	232.20.0500.013		445.2	648	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456	330	36.9
	232.20.0500.503		445.2	648	56	620	505	20	16	18	M12			45.5	10.5	45.5	45.5	545.5	542.5	6	76	456	330	36.7
	232.21.0575.013		445.2	647	56	620	505	10	16	18	M12			45.5	10.5	45.5	45.5	545.5	541	6	76	456	330	36.9
		1.650.20.00.C	445.2	648	56	620	505	10	16	φ18	M12	583		46	10	46	46	545.5	542.5	6	76	456	700	40.2
VLI200644N ZT			546	748	56	720	605	12	18	φ18	M12	688.5		44.5	11.5	44.5	47.5	645.5	642.5	6	93	558	900	47.4
VLI200644N			546	748	56	720	605	12	18	18	M12			44.5	8.5	44.5	47.5	645.5	642.5	6	93	558	455	45
	232.20.0600.013		547.2	748	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558	390	43.7
	232.20.0600.503		547.2	748	56	720	605	24	18	18	M12			45.5	10.5	45.5	45.5	645.5	642.5	6	93	558	390	43.4
	232.21.0675.013		547.2	747	56	720	605	12	18	18	M12			45.5	10.5	45.5	45.5	645.5	641	6	93	558	390	43.7
		1.750.20.00.C	547.2	748	56	720	605	12	18	φ18	M12	683		46	10	46	46	645.5	642.5	6	93	558	780	53.3
VLI200744N ZT			648	848	56	820	705	12	20	φ18	M12	788.5		44.5	11.5	44.5	47.5	745.5	742.5	6	110	660	530	54
VLI200744N			648	848	56	820	705	12	20	18	M12			44.5	8.5	44.5	47.5	745.5	742.5	6	110	660	530	51.5
	232.20.0700.013		649.2	848	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660	450	51.1
	232.20.0700.503		649.2	848	56	820	705	24	20	18	M12			45.5	10.5	45.5	45.5	745.5	742.5	6	110	660	450	50.8
	232.21.0775.013		649.2	847	56	820	705	12	20	18	M12			45.5	10.5	45.5	45.5	745.5	741	6	110	660	450	51.1
		1.850.20.00.C	649.2	848	56	820	705	12	20	φ18	M12	783		46	10	46	46	745.5	742.5	6	110	660	910	63.1
VLI200844N ZT			736	948	56	920	805	14	20	φ18	M12	888.5		44.5	11.5	44.5	47.5	845.5	842.5	8	94	752	1200	65.2

VLI200844N			736	948	56	920	805	14	20	18	M12			44.5	8.5	44.5	47.5	845.5	842.5	8	94	752	600	61.5
	232.20.0800.013		737.6	948	56	920	805	14	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752	510	61.6
	232.20.0800.503		737.6	948	56	920	805	28	20	18	M12			45.5	10.5	45.5	45.5	845.5	842.5	8	94	752	510	61.3

Sichuan MetalMiracle Industry Corp.  
[www.slewingbearing.tech](http://www.slewingbearing.tech)

Address:  
Tianfu Avenue South Section NO.2039, HuaYang, Chengdu Tianfu New Area,  
China.  
Mechanical Industry area, Maanshan, China.  
Industry park, Luoyang, China.